

3590EXT3GD

3590E "ENTERPRISE" 3GD series: WEIGHT INDICATOR FOR ADVANCED APPLICATIONS IN ATEX 2 & 22 ZONES



Weight indicator for ATEX areas classified at risk of explosion with protection methods according to

ATEX II 3G Ex nR IIC T6 Gc X for gases

ATEX II 3D Ex tc IIIC T135°C Dc IP68 X for dust.

The wide range of available software program guarantees the maximum versatility. Completely programmable printouts and fitted with alibi memory. CE-M approvable (OIML R-76 / EN 45501).



Working in cooperation with:

**P.R.S. TORFBUD**

UL.KOPERNIKA 6 - 41500 - CHORZOW - POLAND  
Tel. 0048-322413522 Fax. 0048-322413522  
torfbud@wagielektroniczne.com.pl

**The best solution  
for advanced industrial  
applications**

## MAIN FEATURES

- 25-key alphanumeric waterproof keyboard.
- Highly efficient red LED display with 6 digits 15mm high.
- Backlit LCD graphic 25x100mm display.
- Synoptic bar graph with 16 bright LEDs showing the active functions.
- Easy to clean STAINLESS STEEL waterproof IP68 enclosure; resistant to harsh and corrosive environments.
- Dimensions: 264x115x174 mm.
- Suitable for use on the table, column, or wall.
- Real time clock and permanent data storage.
- Fitted with alibi memory, integrated on the motherboard.
- Functions available with DINI TOOLS utility
  - Configuration, calibration, data entry and print formatting.
  - Recording and filing of all the information on PC.
  - Complete retrieval of the saved data for quick replacement.
  - Instrument calibration with numeric values.
- Selection of the programme language directly in the set-up.
- 24-bit A/D converter, 4 channels, up to 3200 conv./sec. and up to 8 signal linearisation points.
- Up to 10.000e OIML or 3 x 3000e @ 0,3  $\mu\text{V/d}$  CE-M legal for trade.
- Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points.
- 110-240 Vac power supply.
- Management of up to 4 independent scales (up to 2 for the AF03 version).
- Connectable with up to 16 analogue 350-Ohm (or 45 1000-Ohm) load cells.
- Connectable to printers and labellers with the command drivers.

## MAIN CERTIFICATIONS

- EC Type Approval (EN45501)
- OIML R76
- OIML R51 - MID
- OIML R134 (AF09)

## I/O SECTION

- Two RS232 serial ports, for connection to printer (in safety zone), PC or PLC.
- One RS232/RS485 serial port, for connection to printer (in safety zone), PC or PLC.
- 4 optoisolated outputs (16 in the IO versions).
- 2 optoisolated inputs (8 in the IO versions).
- Profibus interface to install in safety zone (available upon request for E-AF01 and E-BATCH1 versions).
- Analogue output with D/A converter at 16 bit, 0-10Vdc, 0-20mA, 4-20mA (available upon request for the IO versions).



www.diniargeo.com



DINI AR GEO  
FRANCE sarl  
Nogent-sur-Marne

DINI AR GEO  
GMBH  
Sinsheim - Germany

DINI AR GEO  
UK Ltd  
Taunton - United Kingdom

DINI AR GEO WEIGHING  
INSTRUMENTS Ltd  
Shanghai - China

DINI AR GEO  
WEIGHBRIDGES  
Calto (RO) - Italy



HEAD OFFICE  
Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena - Italy



### **P.R.S. TORFBUD**

UL.KOPERNIKA 6 - 41500 - CHORZOW - POLAND

Tel. 0048-322413522 Fax. 0048-322413522

torfbud@wagielektroniczne.com.pl

SALES AND TECHNICAL ASSISTANCE SERVICE